

SAFETY DATA SHEET

Issuing Date No data available

Revision Date 10-Jun-2015

Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name SERIES 300CW LOW VOC URETHANE 2606 CLEAR PART A+B

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Paint

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name MERCURY PAINT

Supplier Address 4808 FARRAGUT ROAD
BROOKLYN
NY
11203
US

Supplier Phone Number Phone:7184698787
Fax:7184698787

Supplier Email VGANDHI@MERCURYPAIN.COM

Emergency telephone number

Company Emergency Phone Number CHEMTREC18004249300

2. HAZARDS IDENTIFICATION

Classification


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).



Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3 Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal word	Danger
Hazard Statements	
Causes skin irritation	
Causes serious eye irritation	
May cause an allergic skin reaction	
May cause genetic defects	
May cause cancer	
May damage fertility or the unborn child	
May cause drowsiness or dizziness	
Flammable liquid and vapor	
Highly flammable liquid and vapor	
	
Appearance	Clear
Physical state	Liquid
Odor	Arromatic

Precautionary Statements - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Wear protective gloves/protective clothing/eye protection/face protection
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating/ lighting/ equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool
- Wear eye/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Skin

If skin irritation or rash occurs: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

Not applicable

Other information

May be harmful in contact with skin
Toxic to aquatic life with long lasting effects
Harmful to aquatic life
Repeated or prolonged skin contact may cause allergic reactions with susceptible persons
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION
Exposure to chlorinated hydrocarbons, such as chloroform and trichloroethane, may increase toxic effects
INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Talc	14807-96-6	20 - 30	*
Hexane1,6Diisocyanatohomopolymer	28182-81-2	10 - 12	*
Xylene	1330-20-7	10 - 30	*
Mek	78-93-3	1 - 2	*
Mibk	108-10-1	1 - 2	*
Acrylic aliphatic urethane mixture	Trade secret	25 - 45	*
Butyl acetate	123-86-4	5 - 10	*
Aromatic solvent	64742-95-6	0.1 - 1	*
Pmacetae	108-65-6	8 - 10	

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice

Show this safety data sheet to the doctor in attendance.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin contact

May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Burning sensation. Itching. Rashes. Hives. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

May cause sensitization of susceptible persons. Treat symptomatically.



5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Product is or contains a sensitizer. May cause sensitization by skin contact. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Uniform Fire Code

Sensitizer: Liquid
Flammable Liquid: I-C

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other Information

Refer to protective measures listed in Sections 7 and 8. Ventilate the area.

Environmental precautions

Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways.

Methods for cleaning up

Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc 14807-96-6	TWA: 2 mg/m ³	(vacated) TWA: 2 mg/m ³	IDLH: 1000 mg/m ³ containing no asbestos and <1% quartz TWA: 2 mg/m ³
4-Methylpentan-2-One 108-10-1	TWA 83mg/m ³ TWA 20 ppm	STEL 208mg/m ³ STEL 50ppm	
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	
Pmacetae 108-65-6	TWA: 5 mg/m ³	(vacated) TWA: 5 mg/m ³ (vacated) STEL: 10 mg/m ³	IDLH: 5000 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls



Engineering Measures Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection If splashes are likely to occur. None required for consumer use. Tight sealing safety goggles.

Skin and body protection Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

<p>Physical state Liquid Appearance Clear Color No information available</p>	<p>Odor Ketones Odor Threshold No information available</p>
--	---

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	UNKNOWN	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	24 C / 75.2 F	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	1.21	None known	
Water Solubility	Virtually insoluble	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

Other Information



Softening Point	No data available
VOLATILITY %	35.25%(V/V)25.38%(V/W)
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness and dizziness.
Eye contact	Specific test data for the substance or mixture is not available. (based on components). May cause redness, itching, and pain. Causes serious eye irritation.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Mibk 108-10-1	> 2080 mg/kg (Rat) LD50	1600mg/kg LD50(RABBIT)	100g/m3 LC50(RAT)
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 47635 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Pmacetae 108-65-6	= 6190 mg/kg (Rat)	= 5 g/kg (Rabbit)	> 10.62 mg/L (Rat) 4 h > 23.67 mg/L (Rat) 6 h
Butylacetate 123-864	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h



Aromatic solvent 64742-95-6	-	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h = 3400 ppm (Rat) 4 h
--------------------------------	---	-------------------------	--

Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization of susceptible persons. May cause sensitization by skin contact.

Mutagenic Effects There is no data available for this product. Contains a known or suspected mutagen.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6		Group 3		X
Xylene 1330-20-7		Group 3		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity Contains a known or suspected reproductive toxin.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic Toxicity No known effect based on information supplied. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Contains a known or suspected reproductive toxin. May cause adverse liver effects. Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

Target Organ Effects Respiratory system. Eyes. Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI). Reproductive System. Central Nervous System (CNS). Liver. Lungs. Blood. Kidney. Testes.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
7,406.00 mg/kg



ATEmix (dermal)
4,715.00 mg/kg (ATE)
ATEmix (inhalation-gas)
20,992.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
6.49 mg/l
ATEmix (inhalation-vapor)
47.88 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Butylacetate 123-86-4		96h LC50: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) 96h LC50: 6210 - 8120 mg/L (Pimephales promelas) 96h LC50: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	48h EC50: 10294 - 17704 mg/L 48h EC50: 12600 - 12700 mg/L
Xylene 1330-20-7		96h LC50: = 13.4 mg/L (Pimephales promelas) 96h LC50: 2.661 - 4.093 mg/L (Oncorhynchus mykiss) 96h LC50: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) 96h LC50: 13.1 - 16.5 mg/L (Lepomis macrochirus) 96h LC50: = 19 mg/L (Lepomis macrochirus) 96h LC50: 7.711 - 9.591 mg/L (Lepomis macrochirus) 96h LC50: 23.53 - 29.97 mg/L (Pimephales promelas) 96h LC50: = 780 mg/L (Cyprinus carpio) 96h LC50: > 780 mg/L (Cyprinus carpio) 96h LC50: 30.26 - 40.75 mg/L (Poecilia reticulata)	EC50 = 0.0084 mg/L 24 h	48h EC50: = 3.82 mg/L 48h LC50: = 0.6 mg/L
Hexane1, 6Diisocyanatohomopolymer 28182-81-2	72h EC50: > 130 mg/L (Desmodesmus subspicatus) 96h EC50: > 0.1 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 0.16 mg/L (Pimephales promelas) 96h LC50: > 0.200 mg/L (Lepomis macrochirus) 96h LC50: 0.27 - 0.67 mg/L (Pimephales promelas) 96h LC50: > 0.32 mg/L (Oncorhynchus mykiss) 96h LC50: > 0.32 mg/L (Brachydanio rerio) 96h LC50: > 0.32 mg/L (Oryzias latipes) 96h LC50: > 100 mg/L (Oncorhynchus mykiss) 96h LC50: > 0.32 mg/L (Poecilia reticulata) 96h	EC50 = 800 mg/L 15 min EC50 = 800 mg/L 30 min EC50 = 800 mg/L 5 min	48h EC50: > 0.16 mg/L 48h LC50: = 9.4 mg/L
Talc 14807-96-6		96h LC50: > 100 g/L (Brachydanio rerio)		
Aromatic solvent 64742-95-6		96h LC50: = 9.22 mg/L (Oncorhynchus mykiss)		48h EC50: = 6.14 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Xylene 1330-20-7	3.15
Pmacetae 108-65-6	5.03
Hexane1, 6Diisocyanatohomopolymer 28182-81-2	5.73

Other adverse effects

No information available.



13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated Packaging Do not reuse empty containers.

US EPA Waste Number D001 U028 U239 U154 U002 U031

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239
Butyl acetate 123-86-4	U028	Included in waste stream: F039		U028

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Xylene 1330-20-7	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name CONSUMER COMMODITY
Hazard Class ORM-D
Description CONSUMER COMMODITY, ORM-D

TDG

UN-No. UN1866
Proper Shipping Name RESIN SOLUTION
Hazard Class 3
Packing Group II
Description UN1866, RESIN SOLUTION, 3, II, MARINE POLLUTANT

MEX

UN-No. UN1866
Proper Shipping Name RESIN SOLUTION
Hazard Class 3
Packing Group II
Description UN1866, RESIN SOLUTION, 3, II

ICAO

UN-No. UN1866
Proper Shipping Name RESIN SOLUTION



Hazard Class 3
Packing Group II
Description UN1866, RESIN SOLUTION, 3, II

IATA

UN-No. UN1866
Proper Shipping Name RESIN SOLUTION
Hazard Class 3
Packing Group II
Description UN1866, RESIN SOLUTION, 3, II

IMDG/IMO

UN-No. UN1866
Proper Shipping Name RESIN SOLUTION
Hazard Class 3
Packing Group II
EmS-No. F-E, S-E
Description UN1866, RESIN SOLUTION, 3, II, (27°C C.C.), MARINE POLLUTANT

RID

UN-No. UN1866
Proper Shipping Name RESIN SOLUTION
Hazard Class 3
Packing Group II
Classification code F1
Description UN1866, RESIN SOLUTION, 3, II

ADR

UN-No. UN1866
Proper Shipping Name RESIN SOLUTION
Hazard Class 3
Packing Group II
Classification code F1
Tunnel restriction code (D/E)
Description UN1866, RESIN SOLUTION, 3, II

ADN

UN-No. UN1866
Proper Shipping Name RESIN SOLUTION
Hazard Class 3
Packing Group II
Classification code F1
Special Provisions 640C
Description UN1866, RESIN SOLUTION, 3, II
Hazard Labels 3
Limited Quantity 5 L
Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL All components are listed either on the DSL or NDSL.
IECSC -



TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1330-20-7	10 - 30	1.0
Pmacetae - 108-65-6	108-65-6	8 - 10	

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Pmacetae 108-65-6	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Hexane1, 6Diisocyanatohomopolymer 288182-81-2	Carcinogen Developmental Male Reproductive
Pmacetae	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois



Talc 14807-96-6	X	X	X		
Xylene 1330-20-7	X	X	X	X	X
Barytes 7727-43-7	X	X	X	X	X

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Talc 14807-96-6 (3 - 7)		Mexico: TWA= 2 mg/m ³
Xylene 1330-20-7 (10 - 30)		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 655 mg/m ³
Pmacetae 108-65-6 (8 - 10)	A3	Mexico: TWA 5 mg/m ³ Mexico: STEL 10 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens
A3 - Confirmed Animal Carcinogen

Canada

WHMIS Hazard Class

Not determined

16. OTHER INFORMATION

NFPA	Health Hazards 3	Flammability 3	Instability 0	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 3 *	Flammability 3	Physical Hazard 0	

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Revision Date 10-Jun-2015

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

