

SERIES 6100

AQUAZOOM



PRODUCT FEATURES

- Excellent adhesion to glossy surfaces
- Stain blocking properties
- Dries in minutes
- Binds chalky surfaces
- Interior/Exterior

GENERAL PROPERTIES

An excellent interior/exterior all purpose primer/sealer for most stains such as water, smoke, knots, grease, lipstick, food, magic markers, and graffiti. Aqua Zoom is easy to apply and has excellent hiding power. It kills stains and prevents bleeding into top coat.

RECOMMENDED USES

- Walls
- Ceilings
- Wood
- Plaster
- Concrete
- Gloss enamels
- Sheet rock
- Glass
- Tiles

LIMITATIONS

- Do not use on floors or decks.
- Do not use for immersion.

Finish	Low Sheen
Vehicle Type	100% Acrylic Latex
Pigment Type	Titanium Dioxide
Solvent Type	Water
Coating Category	max VOC 100 g/l
% Solid by Weight	52% +/- 2%
% Solid by Volume	40% +/- 2%
Weight/Per Gallon	10.50 +/-0.20 lbs/gal
Recommended Dry Film by Coat	1.6 mils per coat
Theoretical Coverage	400 sq ft. / gallon on non-porous surface
Dry Time Average	To touch: 30 min To recoat: 1-2 hours Full cure: 30 days
Application Method	Brush, roller, spray
Shelf Life	24 months
Packaged	One and five gallon pails
Flash Point	Over 200°F (93°C)
Colors	White/ tinted colors
Master Painter's Institute	MPI #17



SURFACE PREPARATION

Surfaces should be clean, dry, sound, and free of dust, dirt, excessive chalky material, grime, grease, oil, wax, mildew, wallpaper adhesive or any contamination that may interfere with adhesion. Sand and any remaining paint film edges smooth with the surface. Lightly sand exposed exterior wood with 80 to 100 grit sandpaper to remove loose or weathered wood fibers.

APPLICATION CONDITIONS

Apply when air and surface temperature is between 50°F and 90°F. Relative humidity 85% maximum.

APPLICATION EQUIPMENT

- Brush – Use synthetic nylon/ poly blend brush
- Roller – Any high quality roller
- Spray – Fluid pressure-2,000-2,500 PSI
Tip- 0.15-0.17 orifice

THINNING / CLEAN UP INSTRUCTIONS

If thinning is necessary add no more than 1/2 pint of clean water per gallon. Clean all equipment with warm water and detergent.

ENVIRONMENTAL INFORMATION

Contains no lead, mercury or chromate hazardous compounds. Complies with N.Y., N.J. and other states' requirements for limitation of volatile organic compounds. Meets New York Part 205 architectural surface coatings. Meets criteria for non-photochemical solvents in accordance with New York City Law 49.

Keep out of reach of children.

Protect from freezing.

Material Safety Data Sheets available upon request.

HEALTH & SAFETY INFORMATION

Do not take internally. Close container after each use. In case of skin contact, wipe area with clean cloth and wash thoroughly with soap and water; for eyes, flush with water 15 minutes and get medical attention. If swallowed, get medical attention immediately. Be sure the area is well ventilated while painting is being done. If not, use a suitable respirator.

RECOMMENDED SYSTEMS

Plaster / Drywall New	Primer: Series 6100 Finish: appropriate Mercury Finish Coat
Plaster / Drywall Repainted	Primer: Series 6100 Finish: appropriate Mercury Finish Coat
Wood New	Primer: Series 6100 Finish: appropriate Mercury Finish Coat
Wood Repainted	Primer: Series 6100 Finish: appropriate Mercury Finish Coat
Masonry	Primer: Series 6100 Finish: appropriate Mercury Finish Coat
Masonry Repainted	Primer: Series 6100 Finish: appropriate Mercury Finish Coat
Metal Surfaces	Primer: Series 6100 Finish: appropriate Mercury Finish Coat

ACCURACY OF DATA

The technical data presented above are true and accurate as of the date of issuance of this Mercury Paint data sheet and are subject to change without notice. We endeavor to supply all catalog holders with up-to-date catalog pages. Therefore, if the issue date is more than a year old, please inquire whether a new page has since been issued. Please visit www.mercurypaint.com for the newest version of this data sheet.

WARRANTY

This product is warranted only to conform to the analysis and specifications expressed above. No other warranty or guarantee, including its merchantability or suitability for any specific application, is implied. The liability of Mercury Paint Corporation, if any, is limited to replacement of product or refund of purchase price and excludes labor, cost of labor of other consequential damages, provided that the purchaser notifies management of Mercury Paint Corporation with twenty-four hours of the application of the product.

