



Mercury Paint

Issuing Date No data available

# SAFETY DATA SHEET

Revision Date 25-Jun-2015



Revision Number 1



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publicly available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name SERIES 6400 ALKYD UNIVERSAL MERAL PRIMER WHITE

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Paint

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name MERCURY PAINT

Supplier Address 4808 FARRAGUT ROAD  
BROOKLYN  
NY  
11203  
US

Supplier Phone Number Phone:7184698787  
Fax:7184698787

Supplier Email VGANDHI@MERCURYPAIN.COM

### Emergency telephone number

Company Emergency Phone Number CHEMTREC18004249300

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).


Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A



Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 3

**GHS Label elements, including precautionary statements**

**Emergency Overview**

<b>Signal word</b>	<b>Danger</b>	
<b>Hazard Statements</b>		
May cause an allergic skin reaction		
May cause genetic defects		
May cause cancer		
May cause damage to organs through prolonged or repeated exposure		
May be fatal if swallowed and enters airways		
Flammable liquid and vapor		
		
<b>Appearance</b>	White & Colors	<b>Physical state</b> Liquid
		<b>Odor</b> Phenolic

**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Contaminated work clothing should not be allowed out of the workplace
- Wear protective gloves
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ ventilating/ lighting/ equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge

**Precautionary Statements - Response**

- IF exposed or concerned: Get medical advice/attention
- Specific treatment (see supplemental first aid instructions on this label)

**Skin**

- If skin irritation or rash occurs: Get medical advice/attention
- Wash contaminated clothing before reuse
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

**Ingestion**

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- Do NOT induce vomiting

**Fire**



In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**

Not applicable

**Other information**

May be harmful if swallowed  
Toxic to aquatic life with long lasting effects  
Repeated or prolonged skin contact may cause allergic reactions with susceptible persons  
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

**Interactions with Other Chemicals**

No information available.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	Weight-%	Trade Secret
Titanium dioxide	13463-67-7	20 - 30	*
Alkyd resin polymer	Proprietary	70- 75	*
Aromatic solvent	64742-95-6	5 -15	*
Talc	14807-96-6	10-20	*
Limestone	1317-65-3	10 - 20	*
Zinc oxide	1314-13-2	1-5	*
Methyl propyl ketone	107-87-9	21%	*
Methyl ethyl ketoxime	96-29-7	0.1 - 1	*
Naphtha (petroleum), hydrotreated heavy	64742-48-9	0.1 - 1	*
Acetone	67-64-1	1-2	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

**4. FIRST AID MEASURES**

**First aid measures**

**General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing.



---

**Skin contact**

May cause an allergic skin reaction. In the case of skin irritation or allergic



reactions see a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

- Inhalation**                      Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Seek immediate medical attention/advice. Delayed pulmonary edema may occur.
- Ingestion**                        Aspiration hazard if swallowed - can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.
- Self-protection of the first aider**    Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Remove all sources of ignition.

**Most important symptoms and effects, both acute and delayed**

**Most Important Symptoms and Effects**                      Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

**Indication of any immediate medical attention and special treatment needed**

**Notes to Physician**                                      May cause sensitization of susceptible persons. Treat symptomatically.



## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

### Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

Product is or contains a sensitizer. May cause sensitization by skin contact. Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

#### **Uniform Fire Code**

Sensitizer: Liquid  
Flammable Liquid: I-C

### Hazardous Combustion Products

Carbon oxides.

### Explosion Data

**Sensitivity to Mechanical Impact** No.

**Sensitivity to Static Discharge** Yes.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions**                      Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. See section 8 for more information. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other Information**                              Refer to protective measures listed in Sections 7 and 8. Ventilate the area.

**Environmental precautions**

**Environmental precautions**                Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

**Methods and material for containment and cleaning up**

**Methods for containment**                    Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways.

**Methods for cleaning up**                    Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Handling**    Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

**Conditions for safe storage, including any incompatibilities**

**Storage**    Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Protect from moisture. Store away from other materials. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

**Incompatible Products**                        None known based on information supplied.



**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	TWA: 500PPM STEL: 750PPM	TWA: 2400MG/M <sup>3</sup> TWA: 1000PPM	
Alkyd resin polymer Proprietary	NOT KNOWN	NOT KNOWN	NOTKNOWN
Talc 14807-96-6	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	IDLH: 1000mg/m <sup>3</sup> containing no asbestos and <1% quartz TWA: 2 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	Total dust TWA: 15 mg/m <sup>3</sup> Total duct (vacated) TWA: 15 mg/m <sup>3</sup>	IDLH: 5000mg/m <sup>3</sup>
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (vacated) TWA: 15 mg/m <sup>3</sup> (vacated) TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> respirable dust TWA: 10 mg/m <sup>3</sup> total dust
Zinc oxide 1314-13-2	STEL: 10 mg/m <sup>3</sup> respirable fraction TWA: 2 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> fume (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) STEL: 10 mg/m <sup>3</sup> fume	IDLH: 500 mg/m <sup>3</sup> Ceiling: 15 mg/m <sup>3</sup> dust TWA: 5 mg/m <sup>3</sup> dust and fume STEL: 10 mg/m <sup>3</sup> fume

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

**Other Exposure Guidelines**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992)

**Appropriate engineering controls**

**Engineering Measures**

Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Tight sealing safety goggles.

**Skin and body protection**

Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves. Antistatic boots.

**Respiratory protection**

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.





**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and Chemical Properties**

<b>Physical state</b>	Liquid	<b>Odor</b>	No data available
<b>Appearance</b>	White	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		

<u>Propert</u>	<u>Values</u>	<u>Remarks Method</u>
<b>pH</b>	UNKNOWN	None known
<b>Melting / freezing point</b>	No data available	None known
<b>Boiling point / boiling range</b>	>43 °C / > 109 °F	None known
<b>Flash Point</b>	-4F	None known
<b>Evaporation Rate</b>	No data available	None known
<b>Flammability (solid, gas)</b>	No data available	None known
<b>Flammability Limit in Air</b>		
Upper flammability limit	No data available	
Lower flammability limit	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Vapor density</b>	No data available	None known
<b>Specific Gravity</b>	1.572	None known
<b>Water Solubility</b>	Virtually insoluble	None known
<b>Solubility in other solvents</b>	No data available	None known
<b>Partition coefficient: n-octanol/water</b>	No data available	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known
<b>Explosive properties</b>	No data available	
<b>Oxidizing properties</b>	No data available	

**Other Information**

<b>Softening Point</b>	No data available
<b>Volatility</b>	41:75% (v/v); 22:695% (v/w)
<b>Particle Size</b>	No data available
<b>Particle Size Distribution</b>	



**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available.

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous Polymerization**

Hazardous polymerization does not occur.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

None known based on information supplied.

**Hazardous Decomposition Products**

Carbon oxides.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Product Information**

**Inhalation**

Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

**Eye contact**

Specific test data for the substance or mixture is not available. May cause irritation.

**Skin contact**

Repeated exposure may cause skin dryness or cracking.

**Ingestion**

Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

**Component Information**

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	> 5800mg/kg ( Rat )	20000 mg/kg Rabbit	76 mg/L (Rat) 4hr
Aromatic solvent 64742-95-6	-	> 2000 mg/kg ( Rabbit )	> 5.2 mg/L ( Rat ) 4 h = 3400 ppm ( Rat ) 4 h
Alkyd resin polymer Proprietary	NOT KNOWN	NOT KNOWN	NOT KNOWN
Zinc oxide 1314- 13-2	> 5000 mg/kg ( Rat )	-	-
Methyl ethyl ketoxime 96-29- 7	= 930 mg/kg ( Rat )	= 0.2 mg/kg ( Rabbit )	= 20 mg/L ( Rat ) 4 h
Naphtha (petroleum), hydrotreated heavy 64742-48-9	> 5000 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	-
Titanium dioxide 13463-67-7	>10000 mg/kg (Rat)		



**Information on toxicological effects**

**Symptoms** Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** May cause sensitization of susceptible persons. May cause sensitization by skin contact.

**Mutagenic Effects** There is no data available for this product. Contains a known or suspected mutagen.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Talc 14807-96-6		Group 3		
Acetone 67-64-1		Group 3		x
Titanium dioxide 13463-67-7		Group 2B		x

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

**Chronic Toxicity** No known effect based on information supplied. Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a known or suspected carcinogen. Aspiration may cause pulmonary edema and pneumonitis. Avoid repeated exposure. Prolonged exposure may cause chronic effects.

**Target Organ Effects** Skin. May affect the genetic material in germ cells (sperm and eggs). Respiratory system. Eyes. Gastrointestinal tract (GI).

**Aspiration Hazard** No information available.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)**  
3,068.00 mg/kg



**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Aromatic solvent 64742-95-6		96h LC50: = 9.22 mg/L (Oncorhynchus mykiss)		48h EC50: = 6.14 mg/L
Methyl ethyl ketoxime 96-29-7	72h EC50: = 83 mg/L (Desmodesmus subspicatus)	96h LC50: 777 - 914 mg/L (Pimephales promelas) 96h LC50: 320 - 1000 mg/L (Leuciscus idus) 96h LC50: = 760 mg/L (Poecilia reticulata)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	48h EC50: = 750 mg/L
Naphtha (petroleum), hydrotreated heavy 64742-48-9		96h LC50: = 2200 mg/L (Pimephales promelas)		96h LC50: = 2.6 mg/L
Talc 14807-96-6		96h LC50: >100 g/L (Brachydaniorerio)		

**Persistence and Degradability**

No information available.

**Bioaccumulation**

Chemical Name	Log Pow
Methyl ethyl ketoxime 96-29-7	0.65

**Other adverse effects**

No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

- Disposal methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
- Contaminated Packaging** Do not reuse empty containers.
- US EPA Waste Number** D001

**California Hazardous Waste Codes** 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Zinc oxide 1314-13-2	Toxic

**14. TRANSPORT INFORMATION**



**DOT**

UN-No. UN1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Description UN1263, PAINT, 3, III  
 Emergency Response Guide Number 128

**TDG**

UN-No. UN1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Description UN1263, PAINT, 3, III

**MEX**

UN-No. UN1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Description UN1263, PAINT, 3, III

**ICAO**

UN-No. UN1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Description UN1263, PAINT, 3, III

**IATA**

UN-No. UN1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Description UN1263, PAINT, 3, III

**IMDG/IMO**

UN-No. UN1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 EmS-No. F-E, S-E  
 Description UN1263, PAINT, 3, III, (43°C C.C.)

**RID**

UN-No. UN1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Classification code F1  
 Description UN1263, PAINT, 3, III

**ADR**

UN-No. UN1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Classification code F1  
 Tunnel restriction code (D/E)  
 Description UN1263, PAINT, 3, III



**ADN**

UN-No. UN1263  
 Proper Shipping Name PAINT  
 Hazard Class 3  
 Packing Group III  
 Classification code F1  
 Special Provisions 163, 640E, 650  
 Description UN1263, PAINT, 3, III  
 Hazard Labels 3  
 Limited Quantity 5 L  
 Ventilation VE01

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Complies  
 DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Zinc oxide - 1314-13-2	1314-13-2	1 - 5	1.0

**SARA 311/312 Hazard Categories**

Acute Health Hazard Yes  
 Chronic Health Hazard Yes  
 Fire Hazard Yes  
 Sudden release of pressure hazard No  
 Reactive Hazard No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc oxide 1314-13-2		X		

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive



Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
2-Ethylhexanoic acid - 149-57-5	Developmental

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Talc 14807-96-6	X	X	X		
Titanium dioxide 13463-67-7	X	X	X		
Limestone 1317-65-3	X	X	X		
Zinc oxide 1314-13-2	X	X	X	X	
Cobalt bis(2-ethylhexanoate) 136-52-7			X	X	X

**International Regulations**

Component	Carcinogen Status	Exposure Limits
Titanium dioxide 13463-67-7 ( 10 - 30 )		Mexico: TWA 5 mg/m <sup>3</sup> Mexico: STEL 10 mg/m <sup>3</sup>
Talc 14807-96-6 ( 3 - 7 )		Mexico: TWA= 2mg/m <sup>3</sup>
Limestone 1317-65-3 ( 1 - 5 )		Mexico: TWA= 10 mg/m <sup>3</sup> Mexico: STEL= 20 mg/m <sup>3</sup>
Zinc oxide 1314-13-2 ( 1 - 5 )		Mexico: TWA 5 mg/m <sup>3</sup> Mexico: TWA 10 mg/m <sup>3</sup> Mexico: STEL 10 mg/m <sup>3</sup>

**Canada**

**WHMIS Hazard Class**

Not determined

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards 2</b>	<b>Flammability 3</b>	<b>Instability 0</b>	<b>Physical and Chemical Hazards - Personal Protection</b> X
<b>HMIS</b>	<b>Health Hazards 2 *</b>	<b>Flammability 3</b>	<b>Physical Hazard 0</b>	

**Chronic Hazard Star Legend** \* = Chronic Health Hazard

**Prepared By** Product Stewardship



---

23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501  
25-Jun-2015  
No information available

**Revision Date**  
**Revision Note**

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

